



Introduction

The Atlona **AT-OME-EX-TX-WP-E** is an HDBaseT transmitter for video up to 4K/60 4:2:0, plus embedded audio, control, and USB over distances up to 330 feet (100 meters). It is designed for commercial installations in Europe, and includes interchangeable EU and UK faceplates and brackets. Part of the Omega™ Series of integration products for modern AV communications and collaboration, the OME-EX-TX-WP-E is HDCP 2.2 compliant and transmits RS-232 control signals. With a matching HDBaseT receiver, the integrated USB extension addresses the challenge of connecting between USB devices at remote locations, and is ideal for software video conferencing and touch or interactive displays. The OME-EX-TX-WP-E includes a USB 2.0 host interface for a PC, plus two peripheral devices such as a speakerphone, microphone, or keyboard and mouse. This transmitter is ideal for use with Omega Series receivers as well as switchers with HDBaseT inputs.⁽¹⁾

Applications

- Complete system integration**
 The OME-EX-TX-WP-E and OME-SR21 together provide a compact, yet comprehensive and cost-effective integration solution, with 4K scaling, display control, HDBaseT link testing, and audio system interfacing provided by the receiver.
- Lecture hall and training room applications**
 This transmitter is ideal for extending AV connectivity from an OME-PS62 in a central equipment rack to lecterns as well as remote wall and floor box locations, where presenters can easily access the system.
- Video conferencing**
 The OME-EX-TX-WP-E and a compatible Omega Series receiver or switcher are ideal for soft codec and web-based conferencing applications, with the ability to integrate with PCs, cameras, speakerphones, and microphones.

Key Features

Two-gang enclosure for EU and UK wallplate openings – interchangeable EU and UK trim kits

- Allows inconspicuous installation on a wall, in furniture, or in a floor box. Includes EU and UK faceplates and brackets.
- Meets end user requirements for conveniently accessible yet discreet AV connectivity.

Video, audio, power, and data over category cable utilizing HDBaseT technology

- Transmits up to 330 feet (100 meters) @ 1080p with CAT5e/6 or 4K/UHD using CAT6a/7 cable.
- Uses easy-to-integrate category cable for low-cost, reliable system installation.

USB 2.0 interfacing and extension up to 330 feet (100 meters)

- USB type B interface for connection to a host PC, plus two USB type A ports for peripheral devices such as a microphone, speakerphone, or a keyboard and mouse.
- Provides an ideal USB integration solution for software video conferencing, and applications with interactive collaboration.

4K/UHD capability @ 60 Hz with 4:2:0 chroma subsampling

- Compatible with sources up to 4K/60 4:2:0 and 4K/30 4:4:4.
- Supports HDMI data rates up to 10 Gbps from PCs, media players, and Ultra HD Blu-ray players.

HDCP 2.2 compliant

- Adheres to latest specification for High-bandwidth Digital Content Protection.
- Allows protected content stream to pass between authenticated devices.

Remote PoE (Power over Ethernet) powering

- Industry standard IEEE 802.3af PoE is supplied by an Atlona receiver or switcher over HDBaseT.
- Allows convenient wall, floor box, or furniture installation without the need for local AC power.

Specifications

Video	
Signal	Input - HDMI Output - HDBaseT
Copy Protection	HDCP 2.2
Pixel Clock	300 MHz
UHD/HD/SD	4096x2160 (DCI) @ 60 ⁽²⁾ /30/24 Hz 3840x2160 (UHD) @ 60 ⁽²⁾ /50 ⁽²⁾ /24/25/ 30 Hz 1920x1080p @ 23.98/24/25/29.97/ 30/50/59.94/60 Hz 1920x1080i @ 25/29.97/30 Hz, 1280x720p @ 30/50/59.94/60 Hz
VESA All resolutions are 60Hz	2560x2048 2560x1600 2048x1536 1920x1200 1680x1050 1600x1200 1600x900 1440x900 1400x1050 1366x768 1360x768 1280x1024 1280x800 1280x768 1152x768 1024x768 800x600 640x480
Color Space	YUV, RGB
Chroma Subsampling	4:4:4, 4:2:2, 4:2:0
Color Depth	8-bit, 10-bit, 12-bit

Audio			
HDMI / HDBaseT Pass-Through Formats	PCM 2.0 LPCM 5.1 LPCM 7.1	Dolby® Digital Dolby Digital Plus™ Dolby TrueHD Dolby Atmos®	DTS® Digital Surround™ DTS-HD Master Audio™ DTS:X®
Bit Depth	Up to 24 bits		
Sample Rate	32 kHz, 44.1 kHz, 48 kHz, 88.2 kHz, 96 kHz, 176.4 kHz, 192 kHz		

Resolution / Distance	4K/UHD - Feet / Meters		1080p - Feet / Meters	
HDMI IN/OUT	15	5	30	10
CAT5e	295	90	330	100
CAT6/6a/7	330	100	330	100

USB	
Signal	2.0
Maximum Data Rate	120 Mbps
Internal Hubs	1 USB hub

RS-232	
Port	1 x 3-pin captive screw
Use	Pass-through from control system to sink device
Baud Rates	2400, 4800, 9600, 19200, 38400, 57600, 115200
Data flow	Bidirectional

Indicators	
Indicators:	
POWER	1 x LED, green
LINK	1 x LED, yellow

Connectors	
HDMI	1 x Type A, 19-pin female
HDBaseT OUT	1 x RJ45
HOST	1 x USB Type B
DEVICE	1 x USB Type A
RS-232	1 x 3-pin captive screw

Environmental	Fahrenheit	Celsius
Operating Temperature	+32 to +104	0 to +40
Storage Temperature	-4 to +140	-20 to +60
Operating Humidity (RH)	20% to 90%, non-condensing	

Power	
Consumption	11.68 W (includes 2.5 W for USB, powered by RX)
USB Power	2.5 W USB device interface
BTU/h	39.8

Dimensions (H x W x D)	Inches	Millimeters
EU version	5.98 x 3.19 x 1.77	152 x 81 x 45
UK version	5.79 x 3.44 x 1.77	147 x 87.5 x 45

Weight	Pounds	Kilograms
Device	0.40	0.18

Certification	
Device	CE, RoHS, FCC

Compliance	
NDA-899	Yes

Warranty	
Device	To view the product warranty, use the following link: https://atlon.com/warranty

Footnotes

- (1) The AT-OME-EX-TX-WP-E is not compatible with the AT-UHD-HDVS-300 system for extending USB.
- (2) HDMI input supports up to 4K/UHD @ 60 Hz YUV 4:4:4 8-bit. HDBaseT output supports 4K/UHD @ 60 Hz YUV 4:2:0 only. An input of 4K/UHD @ 60 Hz YUV 4:4:4 will be converted to output 4K/UHD @ 60 Hz YUV 4:2:0.

Copyright, Trademark, and Registration

© 2024 Atlona Inc. All rights reserved. "Atlona" and the Atlona logo are registered trademarks of Atlona Inc. Pricing, specifications and availability subject to change without notice. Actual products, product images, and online product images may vary from images shown here.



The terms HDMI, HDMI High-Definition Multimedia Interface, HDMI trade dress and the HDMI Logos are trademarks or registered trademarks of HDMI Licensing Administrator, Inc.



Dolby, Dolby Atmos, and the double-D symbol are registered trademarks of Dolby Laboratories Licensing Corporation.



For DTS patents, see <http://patents.dts.com>. Manufactured under license from DTS, Inc. DTS, the Symbol, DTS and the Symbol together, and Digital Surround are registered trademarks and/or trademarks of DTS, Inc. in the United States and/or other countries. © DTS, Inc. All Rights Reserved.

All other trademark(s), copyright(s), and registered technologies mentioned in this document are the properties of their respective owner(s).